

Refine Search

Search Results -

Terms	Documents
L2 and (portable or laptop or pda or palmtop)	2

Database:
 US Pre-Grant Publication Full-Text Database
 US Patents Full-Text Database
 US OCR Full-Text Database
 EPO Abstracts Database
 JPO Abstracts Database
 Derwent World Patents Index
 IBM Technical Disclosure Bulletins

Search: L4

Search History

DATE: Sunday, January 21, 2007 [Purge Queries](#) [Printable Copy](#) [Create Case](#)

<u>Set</u> <u>Name</u> side by side	<u>Query</u>	<u>Hit</u> <u>Count</u>	<u>Set</u> <u>Name</u> result set
	<i>DB=PGPB,USPT; PLUR=YES; OP=ADJ</i>		
<u>L4</u>	L2 and (portable or laptop or pda or palmtop)	2	<u>L4</u>
<u>L3</u>	L2 and (portable or laptop or pda or palmtop) same (person or individu\$ or user)	1	<u>L3</u>
<u>L2</u>	(communicat\$6 or wireless\$2 or remot\$3)same drill\$3 same rig same (off- site or exterior) same locat\$6	16	<u>L2</u>
<u>L1</u>	(5504491 or 5730219 or 6867752 or 20040190374).pn.	4	<u>L1</u>

END OF SEARCH HISTORY

[First Hit](#) [Previous Doc](#) [Next Doc](#) [Go to Doc#](#)

End of Result Set

☐ [Generate Collection](#) [Print](#)

L4: Entry 2 of 2

File: PGPB

Oct 17, 2002

DOCUMENT-IDENTIFIER: US 20020149617 A1

TITLE: Remote collaboration technology design and methodology

Detail Description Paragraph:

[0060] Referring to FIG. 4-A, the RGBHV video outputs of a computer, such as High-End Visualization machines (1), Mainframe computers (2), Desktop Workstations (3), and PCs (4), are sent into a signal conditioner and amplifier (5), one each for each RGBHV output on each computer source. Many standard types of computers 1, 2, 3, 4 could be used in accord with the present invention (e.g., IBM, SGI, Sun servers, mainframes and workstations, Compaq, Dell, HP Gateway desk-side and laptop PCs, etc.). The signal conditioner 5 is used to boost the RGBHV signals for transmission to the matrix switch 10 and to "normalize" the signals across the various computer sources 1, 2, 3, 4.

Detail Description Paragraph:

[0240] In the energy industry, workers on offshore rigs can better understand the location of a well bore by visualizing the well bore in real-time while drilling is occurring with its associated 3D seismic data which is kept onshore and visualized using high-end graphics computers. While exploration prospects are being evaluated on seismic data, remote collaboration capabilities that include full computer interaction allow experienced off-site interpreters to be brought in and out of the interpretation process without having to travel around the globe. Instead, Remote Collaboration sessions with computers can be used to gain immediate access to key personnel wherever they are.

[Previous Doc](#) [Next Doc](#) [Go to Doc#](#)